



SPF	·()/=/	'CA7	

DESCRIPTION
MODEL - LAD 2016
GVWR - 16,000 lbs.
Over All Length - appox. 29 ft. 6 in. (Approximate)
Over All Width - 102 in.
Empty Weight - 8,000 lbs.
RUNNING GEAR
Axle - 8,000 lbs.
Brakes - Electric
Single Tires - 4) ST215/75R17.5 Load Range (H)
Wheels - 17.5 x 6.75 8 Bolt White mod
FRAME
Main Frame - 10 in. Junior I-beam
Cross Members - 3 in. Channel
Gooseneck Tongue - 10 in. Junior I-beam
LOWER DECK
Size - 20 ft. Long x 97 in. Wide
Material - 2 x 8 Treated kiln dried pine
TOP DECK
Size - 29 ft 6 in. x 92 in.
Center Landing - 20 ft. Long x 92 in. Wide
Material - 2 x 8 Treated kiln dried pine
Cross Members - 2 x 2 x 3/16" Angle
ELECTRICAL
Plug - 7 Way Molded Plug
Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped
Lights - Standard LED package
SAFETY
Chains - Rated to match
Break Away - Battery, battery box, and switch
Decals - Warning decals & reflective tape
ACCESSORIES
Dual Jacks - 12K Side wind with drop legs
Tiedowns - E-Track on top and bottom deck
FINISH
PPG Paint - Industrial urethane- Black, Orange, Yel, White

ADDITIONAL OPTIONS	
Dual Hydraulic Jacks - Electric over hydraulic	
Bumper Pull Setup - 4 x 6 in. Rec Tube	
Dual Side Platforms - 20 ft. Long x 6 ft. Wide	
Single Side Platforms - 20 ft. Long x 6 ft. Wide	
Seed Delivery - Vacuum System	





